



Globally Proven
Construction Solutions

SPARTACOTE™ Polyaspartic Pigments

SPARTACOTE™ Polyaspartic Pigments are designed to be used exclusively with SPARTACOTE FLEX SB™, SPARTACOTE FLEX XT™ and SPARTACOTE FLEX PURE™ polyaspartic coatings. Available in 14 standard colors, these materials are manufactured through a proprietary process in which raw pigment elements are ground and subsequently combined with the highest quality polyaspartic resins available. Once ready for use, these concentrated pigments are dispersed directly into short-filled part A pigment base.



ADVANTAGES

- 14 standard colors, including safety colors
- UV stable, suitable for exterior applications
- Excellent color hide and retention
- Easy to use on-site color dispersion system

USES

- Suitable for interior or exterior applications

MANUFACTURER

LATICRETE Middle East LLC.
P.O. Box. 86028, Ras Al
Khimah
United Arab Emirates
Telephone: + 971 7 244 6396
Fax: + 971 7 244 5915
Internet: www.laticrete.me

PACKAGING / COLOR

Packaging

- 1 qt (0.9 L) for .75 gal (2.8 L) part A base
- 1.25 gal (4.7 L) for 3.75 gal (14.2 L) pigment base

Available in 14 standard colors including safety colors pre-dispersed form upon request. SPARTACOTE FLEX SB polyaspartic coating is available in a White.

Suitable Substrates

As per SPARTACOTE™ Polyaspartic Coating

Approximate Coverage

See applicable SPARTACOTE Polyaspartic Coatings coverage chart

Shelf Life

Three years unopened. Store at 40°F to 75°F (4°-24°C) in a covered area (out of the sun). Maintain a consistent storage temperature prior to application. Material should be kept in a cool dry place prior to application.

Limitations

Refer to data sheet for applicable SPARTACOTE Polyaspartic Coatings

Cautions

- Refer to Safety Data Sheet (SDS)

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

TECHNICAL DATA**Applicable Standards and Test Methods****Physical and Working Properties**

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE Middle East LLC. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

INSTALLATION**Mixing**

Note: Maintain a consistent storage temperature prior to application. Material should be kept in a cool dry place prior to application. Use

only with SPARTACOTE™ FLEX SB™, SPARTACOTE FLEX XT™ and SPARTACOTE FLEX PURE™ polyaspartic coatings.

Pigmented Coatings: Add full contents of SPARTACOTE Polyaspartic Pigments directly into short filled Part A Tint Base. Mix pigment into Part A with a slow speed drill mixer for 2 minutes to fully disperse the resin pigments. Failure to properly mix pigments may lead to an inconsistent finish and reduced product performance.

AVAILABILITY AND COST

Availability: LATICRETE materials are available worldwide. For Distributor information, call: + 971 7 244 6396

Cost

Contact a LATICRETE Distributor in your area.

WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year.

Contact Technical Support for further information

MAINTENANCE

LATICRETE® products are of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending of the cleaning products used.

TECHNICAL SERVICES

Information is available by calling the LATICRETE Technical Service

Telephone: + 971 7 244 6396

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at

www.laticrete.me / www.laticrete.com

Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® unable to directly control the installation conditions and modalities of application of products, do not assume any liability arising from their implementation. Those who want to use the LATICRETE® products must conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.